

CAR-O-LINER®



SPEED™ 3T/SPEED™ 3T PLUS
VERSATILITY SPEEDS THINGS UP

SPEED™ 3T / SPEED™ 3T PLUS

VERSATILITY SPEEDS THINGS UP

Speed 3T is one of the most effective lighter weight benches on the market. Now with the ability to carry up to 3 tons in weight, there isn't much that this bench can't tackle in the way of cosmetic damage repair. It only takes a few seconds to set up the convenient draw aligner which

can be rotated 180° around the platform at one end and tilted 90° horizontally. Once pulling begins the draw aligner finds the correct position. For more pulling power there is the **Speed 3T Plus** bench, which allows the attachment of two draw aligners, one at either end.

SPEED UP THE REPAIR PROCESS

REMOVABLE LIFTING ARM

With telescopic lifting pads that can be adjusted vertically, moved along a rail on each side of the platform, and rotated 180° horizontally.

WORKING PLATFORM

Choose the most suitable working height.

SCISSOR STRUCTURE

Constructed in high strength materials to make 3 ton lifting easy and fast.

STRONG AND SECURE

Large cylinder shaft and super strong pivot pin provide safe, secure lifting of heavier vehicles.

3,000 kg (6,600 lbs)

Maximum vehicle weight

POWER UNIT

Upgraded power unit with more capability and safety built in.




104 - 1600mm | 4.1- 63in

Drive/roll almost any vehicle over the platform, then raise it to maximum lifting height for easy vehicle access

DRIVE-ON RAMP KIT

No need for extra arms. Repair work can begin immediately. Ramps are easily lifted on/off the bench as desired. (Optional)



THE SPEED™ 3T SCISSORLIFT HAS SUCH A LOW PROFILE THAT YOU CAN DRIVE/ROLL ALMOST ANY VEHICLE OVER THE PLATFORM, ELIMINATING THE NEED FOR RAMPS OR EXTERNAL ACCESSORIES.

LIGHT

BUT NOT A LIGHTWEIGHT

VERSATILITY IMPROVES WORKFLOW

Speed 3T can handle most types of sheet metal damage, but what makes this bench different from most ordinary alignment benches is that Speed's versatility allows you to complete almost the entire repair job using just one bench. All service and repair operations can be performed quickly and effectively using a single setup. You avoid the unnecessary interruptions that arise when moving the car between different work stations which gives you a greatly improved workflow and increases your overall workshop capacity.

THE LIFTING PLATFORM IS EASY TO INSTALL, IT ONLY NEEDS TO BE ANCHORED TO THE FLOOR AND IT IS READY TO BE USED. THE 5-TON DRAW ALIGNER GIVES 360° MULTI-ANGLE PULLING POWER. USE TWO ON SPEED PLUS FOR EVEN MORE POWER. SPEED UP — INCREASE THE NUMBER OF REPAIRS AND YOUR SHOP'S BOTTOM LINE.

ERGONOMY ENHANCES PRODUCTIVITY

Speed 3T offers superior vehicle access since no posts are needed, and vehicles can be quickly and easily raised to the most comfortable working height for each repair operation. These ergonomic features increase efficiency and offer a productive working environment.

SPEED AND STRENGTH

High precision guaranteed — the **Speed 3T** lifting platform is the ideal choice for lighter vehicle repairs. Even better, by attaching a draw aligner one may perform alignment work on collision-damaged vehicles. **Speed 3T** is suitable for most passenger cars and light transport vehicles.

ADD PULLING POWER WITH SPEED™ PLUS

Choose **Speed 3T Plus** for when you need double pulling power. This longer version of **Speed 3T** allows the attachment of two draw aligners, so pulling can be done from both ends simultaneously.

FEATURES AND BENEFITS

- **INCREASED LIFTING CAPACITY** — now 3000kg | 6600lbs !
- **5-TON DRAW ALIGNER** — 360° multi-angle pulling
- **QUICK SET-UP TIME** increases workshop capacity
- **LOW PROFILE** — Roll/drive the vehicle over the bench and get started right away on the repair
- **VERSATILE** — handles most types of damage and cosmetic damage repair
- **SINGLE SETUP** — the entire repair job can be completed using one bench, shortening cycle times and increasing profits
- **TWO MODELS** — **Speed 3T** or the longer **Speed Plus 3T**, bring versatility to your repair shop, both also available in Grey.
- **ERGONOMIC DESIGN** — easily reach damaged areas
- **TWO TYPES OF INSTALLATION**, above or flush mounted, gives versatility to complete damage repairs as well as light service or repair work
- **SMALL FOOTPRINT** makes it the perfect addition to any type of repair/service shop
- **ACCURATE REAL-TIME MEASURING** when used with the **Car-O-Tronic®** measuring system and the **Car-O-Data®** vehicle measurement database



PRODUCT INFORMATION


AND TECHNICAL DATA

COMPONENTS

ARTICLE	ART. NO.	QTY.
BS15 Speed 3T, Cpl. with Lift, Blue	50802	1
BS15 Speed 3T, Cpl. with Lift, Grey, RAL 7012	50802-11	1
BS16 Speed Plus 3T, Cpl. with Lift, Blue	50803	1
BS16 Speed Plus 3T, Cpl. with Lift, Grey RAL 7012	50803-11	1
T607 Power Unit, 400V/3ph/50-60 Hz	50871	1
B637 Speed Lift Arm Extension, 60mm	32868	4
D20 Speed Draw Aligner without pump & cylinder	33045	1
D162 Pump D45 & Cylinder D39 for D20	35885	1
B660 Speed Bench Mount Parts: Inc. B30 (4pcs), B106 (4pcs), T32 (1pc)inc	35898	1

OPTIONAL ACCESSORIES

ARTICLE	ART. NO.	QTY.
MC23 Car-O-Tronic Vision2 X3	46733	1
M13 Measuring Bridge 3500mm	32023	1
M420 Speed Support for measuring bridge	34765	1
M421 Spacer Kit for M420	34790	1
B649 Speed Extension for measuring, blue	34386	4
B649 Speed Extension for measuring, grey	34386-11	4
B68 Drive-on ramp kit (incl. Rubber Pad Kit 46870)	46847	1
B735 Rubber block kit, 3 x 4 pcs	46870	1
T56 Wheel Stands (high lift)	30554	4
D201 Speed Side Pull Support	33001	1
D92 Down Pull	32992	1
B661 Speed Bench Mount Parts: Inc. B30 (4pcs), B639 (4pcs), T32 (1pc)	35898	1
B636 Speed Chain Holder	32967	1
B637 Speed Extension 60mm	32888	1
B638 Speed Inboard Extension Arm, 60 mm	32984	1
T500 Speed Connection Kit	33034	1
T250 Cable/Hose Protection	31040	1
T251 Cable/Hose Protection 45°	33286	1



LIFTING PLATFORM	SPEED 3T	SPEED 3T PLUS
Length	2510mm 98.8in	2883mm 113.5in
Width	766mm 30.15in	766mm 30.15in
Min. height	104mm 4.1in	104mm 4.1in
Max. height	1600mm 63in	1600mm 63in
Work area size	3600 x 2966mm 141.7x116.7in	5064 x 2966mm 119.4x116.8in
Total weight, lift + work platform	550 - 600kg 1212 - 1322lbs	550 - 600kgs 1212 - 1322lbs
Lift capacity (max. vehicle weight)	3000kg 6614lbs	3000kg 6614lbs
HYDRAULICS		
Pulling force per draw aligner	5 tons 11000lbs	5tons 11000lbs
Hydraulic pressure on lift	290 bar 4200 psi	290 bar 4200 psi
Air connection pressure max bar (max psi)	10 bar 145 psi	10 bar 145 psi
Sound level db(A)	Below 70	Below 70
Electrical cable length	4m 157.48 ft.	4m 157.48ft.
Hydraulic hose length	7m 275.5ft.	7m 275.5ft.
Cable to control box	10m 393.7ft.	10m 393.7ft.
Power	230/400 V, 3 ph, 50Hz / 220V, 1 ph, 50/60Hz	



CAR-O-LINER®

www.car-o-liner.com



Car-O-Liner (2021) is a trademark of Snap-on Incorporated. All rights reserved.

Product images are for illustrative purposes only and may differ from the actual product. Car-O-Liner reserves the right to modify any content without prior notice.